
WICANDERS
WISE



Natural Performance

AMORIM CORK FLOORING



Wicanders Wise has a legacy that goes back to 1868. It is part of Amorim Cork Flooring, the global leading brand in cork-based flooring solutions, present in more than 80 countries worldwide.

With respect for nature as one of its core values, Wicanders Wise has developed durable and sustainable flooring and wall covering solutions with the exclusive comfort provided by cork. Its portfolio is 100% PVC free and has a remarkable negative carbon balance, helping to reduce global warming potential.

By combining state of the art technology with this unique raw material, we achieve the highest standard in flooring.

Available with Cork, Wood and Stone visuals, Wicanders Wise cork floors endure impacts and are very comfortable to walk and stand on, while providing a silent and thermally insulated environment.

A new level of realism in flooring



Wicanders Wise celebrates an important milestone, and we proudly introduce a 100% PVC free product portfolio, showcasing our unwavering commitment to sustainability and eco-conscious design.

With our new digital printing collection, Wicanders Wise offers a wide range of natural products, with an exceptional level of realism, brought to life through cutting-edge technology.

Feel the intricate texture of wood and the softness of stone – every knot and grain are carefully designed and replicated in an exquisite selection of visuals that will defy the senses.

Discover our latest collections, 100% PVC free, 100% realistic and 100% powered by the unmatched comfort of cork.

Natural Performance

- Unprecedented level of realism with natural texture
- Unlimited design possibilities
- Premium cork comfort
- Negative carbon balance
- Made of renewable resources
- Highly resistant and exceptionally durable
- Suitable for all residential and commercial areas


WICANDERS WISE

SILENCE

SILENCE
Reduces the walking sound up to 53%.




IMPACT RESISTANCE



NATURAL THERMAL INSULATION

INFRARED FOOT TEMPERATURE



NATURAL THERMAL INSULATION
Optimal temperature all year round.

INDOOR AIR QUALITY




INDOOR AIR QUALITY
Compliance with the strictest indoor air quality standards after being tested on over 2000 potential chemicals.



WALKING COMFORT

WALKING COMFORT
Wicanders Wise floors are the perfect mix to reduce heel strike impacts and related body tensions, but stable enough to help the foot impulse and provide the needed stability to reduce effort on walking and decrease body fatigue.





Mountain Oak








wood Start Resist Eco

Start Resist ECO is an entry-level PVC-free floating floor for residential and moderate traffic commercial areas. Its multilayered structure has an integrated cork underlay of 2.2mm which provides comfort and thermal insulation. Designed to last, this cork floor is a great option for those looking for a sustainable solution that combines performance and design. Available in a curated selection of wood visuals to fit any decor style and space.

- 1 PVC-FREE PROTECTIVE WEAR LAYER
- 2 HIGH RESOLUTION DECORATIVE FILM
- 3 NATURAL FIBER CORE
- 4 INTEGRATED CORK UNDERLAY



PRODUCT INFORMATION

| | |
|-------------------------|--|
| Dimension | 1220 x 185 mm |
| Thickness | 7,5 mm |
| Bevel | 4 Sides micro bevel |
| Finishing |  |
| Locking system |  2G |
| Class of use & Warranty | <div></div> |



80003129 - *Mountain Oak*



80003130 - *Sprucewood*



80003131 - *Highland Oak*



80003132 - *Manor Oak*



80003133 - *Ocean Oak*















80003134 - *Field Oak*



80003135 - *Mocca Oak*



80003136 - *Quartz Oak*

| | |
|---|--|
|  | CE CE marking indicates conformity with health, safety and environmental standards for products sold within the European Economic Area (EEA). |
|  | DAS KORK Assures the quality of cork products, as well as the optimization of manufacturing processes and the support of research projects. |
|  | FRENCH REGULATION ON VOC EMISSIONS French certification that classifies products according to their level of voc emissions. Our products have been classified at the highest level (A+). |
|  | TÜV-PROFICERT Tuv-Proficert is a transnational certificate for voc-emission and air quality, certifying that a product complies with different national regulations. |
|  | BLUE ANGEL Voluntary certification that follows strict environmental standards and is recognized as a reference guide for a more sustainable way of life. |
|  | GREENGUARD CERTIFICATION North-american certification that identifies products that have low chemical emissions, improving the air in which they are used. Our products are awarded with the GOLD certification. |
|  | EPD (ENVIRONMENTAL PRODUCT DECLARATION) Third-party independent evaluation that reports environmental data of products based on their life cycle assessment. |
|  | LEED Wicanders products contribute with points in the following categories: Materials and Resources / Indoor Environmental Quality. |
|  | BREEAM Wicanders products contribute with points in the following categories: Health and well being / Materials. |
|  | M1 Presents emission requirements for building materials, fixture and furniture used in office and residential buildings with respect to good indoor air quality. |
|  | HEALTH PRODUCT DECLARATION Provides full disclosure of potential chemicals of concern in products by comparing product ingredients against a set of prioritized red lists. |
|  | NORDIC SWAN ECOLABEL Is one of the world´s toughest environmental certifications, and a powerful tool for producers and brand owners, that offers a recipe on how to reduce the environmental impact from production to consumption of goods, and credible third party certified guidance for their consumers and professional buyers. |

WICANDERS
WISE

TECHNICAL DATA SHEET

woodStart Resist Eco

| Technical Data Sheet | Standard | Unit | Value |
|---|---|---|---|
| Dimension (LxWxT) | - | - | 1220x185x10,5mm |
| Mass per unit | - | Kgs / m² | 8,37 |
| Packaging (box / pallet) | - | m² | 2,483 / 99,32 |
| Level of use Domestic | ISO 10874 | Class | 23 |
| Level of use Commercial | ISO 10874 | Class | 32 |
| General properties - EN 16511 | | | |
| Thickness, t - | ISO 24337 | $\Delta t_{avg} \leq 0,50$ mm, relative to nominal value / $t_{max} - t_{min} \leq 0,50$ mm | Complies |
| Length, l | ISO 24337 | ≤ 1500 mm: $\Delta l \leq 0,5$ mm / > 1500 mm: $\Delta l \leq 0,3$ mm/m | Complies |
| Width, w | ISO 24337 | $\Delta w_{avg} \leq 0,10$ mm, relative to nominal value / $w_{max} - w_{min} \leq 0,20$ mm | Complies |
| Squareness, q | ISO 24337 | $max \leq 0,20$ mm | Complies |
| Straightness, s | ISO 24337 | $max \leq 0,30$ mm/m | Complies |
| Openings, o | ISO 24337 | $max \leq 0,20$ mm | Complies |
| Height difference, h | ISO 24337 | $h_{max} \leq 0,15$ mm | Complies |
| Flatness of the panel (Length - concave / convex) | ISO 24337 | concave $\leq 0,50$ %, / convex $\leq 1,0$ % | Complies |
| Flatness of the panel (Width - concave / convex) | ISO 24337 | concave $\leq 0,15$ %, / convex $\leq 0,20$ % | Complies |
| Classification properties - EN 16511 | | | |
| Wear resistance IP | EN 15468, procedure B | $\geq 5\,000$ cycles | Complies |
| Impact resistance [mm] (big ball) | EN 13329:2006+A1:2008, Annex F | $\geq 1\,600$ mm | Complies |
| Castor chair resistance | EN 425 | 25 000 cycles | Complies |
| Resistance to staining | EN 438–2 | Groups 1 and 2: grade 5 Group 3: grade 4 | Complies |
| Residual Indentation | EN ISO 24343-1 | $\leq 0,2$ mm | Complies |
| Swelling | ISO 24336 | $\leq 18\%$ | Complies |
| Safety properties - EN 14041 | | | |
| Fire resistance | EN ISO 11925-2 + EN ISO 9239-1 : Class EN 13501-1 | Class | E |
| Slip Classification | EN 13893 | Class | DS |
| Formaldehyde emission | EN 717-1 | Class | E1 |
| Content pentachlorophenol (PCP) | "EN 14041 Annex B" | mg/kg | Undetectable |
| Thermal resistance (Thermal conductivity) | EN ISO 10456 | m²·K/W | 0,065 |
| Additional properties | | | |
| Sound Pressure Level | EN ISO 10140 | dB (Δ Lw) | 5,8 |
| Walking noise | IHD-W431 | dB % | Difference of loudness 10,4dB Reduction improvement 40% |

- 1

PVC-FREE PROTECTIVE WEAR LAYER
- 2

HIGH RESOLUTION DECORATIVE FILM
- 3

NATURAL FIBER CORE
- 4

INTEGRATED CORK UNDERLAY



Amorim Cork Flooring, S.A.

Rua do Ribeirinho 202 - P.O. Box 13

4536-907 S. Paio de Oleiros - Portugal

T. +351 22 747 56 00 E. info.acf@amorim.com



www.wicanders.com

| | | | |
|----------|--------------------------------|--------------------|--|
| DE | Amorim Deutschland GmbH | (+49) 4221 5 93-01 | info.acf.de@amorim.com |
| BENE LUX | Amorim Benelux B.V. | (+31) 166 604 111 | info.acf.bnl@amorim.com |
| AT | Amorim Deutschland GmbH | (+43) 154 51 65 10 | info.acf.at@amorim.com |
| CH | Amorim Flooring Switzerland AG | (+41) 41 726 20 20 | info.acf.ch@amorim.com |
| PT | Amorim Cork Flooring, S.A. | (+351) 227 475 600 | info.acf@amorim.com |
| ES | Amorim Cork Flooring, S.A. | (+351) 227 475 600 | info.acf.es@amorim.com |
| FR | Amorim Cork Flooring, S.A. | (+33) 800 914 848 | info.acf.fr@amorim.com |
| DK | Timberman Denmark A/S | (+45) 995 252 52 | timberman@timberman.dk |
| PL | Dom Korkowy, Sp. z o.o. | (+48) 126 379 639 | krakow@domkorkowy.pl |
| US | Amorim Flooring North America | (+1) 410 553 60 62 | info.acf.us@amorim.com |
| RU | Amorim Flooring Rus, OOO | (+7) 495 280 7860 | info.acf.ru@amorim.com |
| IT | Amorim Cork Flooring, S.A. | (+39) 068 635 7287 | info.acf.it@amorim.com |
| FI | Korkkitrio Oy | (+358) 50 554 2616 | wicandersmyynti@korkkitrio.fi |
| SW | Amorim Flooring Sweden | (+46) 311 077 40 | info.acf.se@amorim.com |
| CA | Amorim Flooring Canada | (+1) 548 457 2240 | sales.afcan@amorim.com |



INVESTORS IN PEOPLE™
We invest in people Standard

Recognised by EFQM
★★★ 2021

AMORIM