## Wood hydr≜cork

Hydrocork is a low thickness and waterproof floating solution that combines extreme performance with the comfort of cork. The innovative core made of composite cork is waterproof and incredibly stable, while its surface offers a wear resistance suitable for heavy commercial areas.

The product's low thickness makes it also the optimal choice for renovation projects. The revolutionary PressFit compression system allows for a fast and easy installation.



1225 x 195 x 6mm 487/32 x 7 11/16 x 1/4"



Century Morocco Pine



## Reclaimed

Reclaimed wood visuals look great in a commercial space such as a boutique coffee.

The strong antique looking flooring has the ability to add history, character and personality to any space.



Sylvan Gold Oak

4 **■** | 0,7mm

1225 x 195 x 6mm



Sylvan Brown Oak

B5WQ001

1225 x 195 x 6mm

















Sawn Bisque Oak

B5P3002 1225 x 195 x 6mm

25 x 195 x 6mm 4 ≥ 10,7mm



Sawn Twine Oak

B5P2002

1225 x 195 x 6mm

#### wood Hydrocork



Castle Raffia Oak

B5P0002 1225 x 195 x 6mm

4 **■** | 0,7mm



Castle Toast Oak

B5P1002

1225 x 195 x 6mm



# Tradition No problem. It's ready for real life.

An open plan kitchen must boast a stylish vibe and sense of wellbeing with measured sobriety.

With Hydrocork, you no longer need to be worried if the floor is able to endure the test of time in a gracious way and how it resists impacts. You don't even need to fear over daily spillings due to its waterproof endurance.

Take advantage of it being ideal for renovations and place it on top of previously existing surfaces, or simply achieve a total look throughout your home with the same look in your kitchen, living room, bathroom and bedrooms.

 $Ten \ Traditional \ wood \ looks \ to \ choose \ from \ and \ complement \ with \ industrial, \\ minimal ist \ or \ even \ rustic \ designs.$ 



European Oak
B5Q2002
1225 x 195 x 6mm 4 M 1 0.7mm



Nature Oak

B5T5002

1225 x 195 x 6mm 4 10.7mm





Elegant Oak

B5R4002

1225 x 195 x 6mm 4 10.7mm





4 **■** | 0,7mm

Sand Oak B5R1002 1225 x 195 x 6mm



4 🕍 | 0,7mm

Wheat Oak B5WR001

1225 x 195 x 6mm



Linen Cherry

B5R0002 1225 x 195 x 6mm

4 **■** | 0,7mm





Light Beech B5T0002 1225 x 195 x 6mm 4 **■** | 0,7mm



Wheat Pine

B5R3002

1225 x 195 x 6mm





## Nordic

This style is characterized by simple yet rich decor elements. Mixing different clean cut chairs can be the fun approach that will help to provide life without loosing the functionality that is part of the Nordic design.



Arcadian Artic Pine B5WT001 1225 x 195 x 6mm 4 **■** | 0,7mm









Claw Silver Oak B5V3003 1225 x 195 x 6mm



Limed Grey Oak B5T7002 1225 x 195 x 6mm 4 **■** | 0,7mm



Cinder Oak B5R7002 1225 x 195 x 6mm 4 **■** | 0,7mm

#### wood Hydrocork

1225 x 195 x 6mm



Arcadian Soya Pine B5P4003

4 **■** | 0,7mm



Arcadian Rye Pine B5P5003 1225 x 195 x 6mm



Century Fawn Pine B5P7002 1225 x 195 x 6mm

4 M | 0,7mm



Century Morocco Pine B5P6002

4 M | 0,7mm

1225 x 195 x 6mm

## Cottage Places where life is celebrated every day.

Flooring can either be the focal point of a room, or a background that aggregates other design elements. It's important to have a clear goal in each new design project in order to guarantee a consistent layout. When you've that figured out, it's with ease that you'll be able to extend your personality into your special space.

A bedroom should mirror relaxation and comfortable atmosphere to provide only pleasant moments. For a modern Cottage style that will be wrapped up with flooring as the background, choose a darker flooring hue that will enable the other decor elements to pop up.









Rustic Fawn Oak

B5WU001 1225 x 195 x 6mm

x 195 x 6mm 4 **1** 10,7mm

### wood Hydrocork



Alaska Oak B5Q0002 1225 x 195 x 6mm





Chalk Oak B5Q1002

1225 x 195 x 6mm 







Light Dawn Oak B5WS001

1225 x 195 x 6mm 4 **■** | 0,7mm



Rustic Grey Oak

B5WV001 1225 x 195 x 6mm



## Technical solution

PROTECTIVE WEAR LAYER

HIGH RESOLUTION DECORATIVE

SOLID VINYL LAYER

AGGLOMERATED CORK COMPOSITE CORE WITH PRESSFIT 3MM

BALANCING VINYL LAYER



Greenguard Certification helps the identification of interior products and materials that have low chemical emissions, improving the quality of the air in which the products are used. It promotes global sustainability, environmental health, and safety.



TÜV-PROFICERT-product Interior brand is a voluntary, independent label for VOC-emission and quality of floorings. The results comply with the emission thresholds of AgBB, Belgian VOC regulation, Finnish M1 classification, BREEAM Exemplary Level, LEED v4 (outside North America), RAL-UZ 120 and Austrian Eco Label (Guideline UZ 56).



As of January 2012, France has adopted regulations that limit total VOC emissions of building products. Manufacturers, selling their products in France must obtain a classification ranging from A+ (very low emissions) to C (high emissions). The declared goal is to improve indoor air quality in private/ commercial buildings.



An Environmental Product Declaration is a verified document that reports environmental data of products based on life cycle assessment and other relevant information in accordance with the international standard ISO 14025.



CE marking is a certification mark that indicates conformity with health, safety and environmental protection standards for products sold within the European Economic Area (EEA).





8 POINTS

## Finishing & Warranty



Suitable for Heavy Traffic Residential areas and Heavy Traffic Commercial areas.











| wood Hydrocork  |
|---|
| 1225 x 195 x 6mm   487/32 x 711/16 x 1/4*   |
| 23  |
| 33  |
| 0,55mm Wear Layer   |
|   |
| ISO 10582 + EN 14085 + EN 14041   |
| ± 0,10 up to<br>max 0,5<br>max 2,0  |
| ±0,25   |
| ≤0,50   |
| ≤0,30   |
| ≤0,50/≤1,0  |
| ≤0,10 /≤0,15  |
| ≤0,20   |
| ≤0,20   |
| ≤5  |
| Nominal +13% / -10%   |
| ≥6  |
|   |
|   |
| -   |
| No disturbance to the surfacen other than slight change in appearance and no delamination shall occur in the surface of the s |
| No damage shall be visible after testing with a type 0 foot   |
| ≤0,1  |
|   |
|   |
| Bfls1   |
| DS  |
| El  |
|   |
| Undetectable<br>  |
|   |
| Grade 0 (b)<br>lodine grade 2 (b)   |
| 0,05  |
| 16 dB   |
| Reduction improvement 11,1dB<br>Difference of loudness 51,1%  |
|   |

<sup>(</sup>a) The following products were tested: Desinfectant,  $C_2H_0OH$ ,  $NH_4OH$ , Citric acid, iodine, petroleum, spirit (b) Grade 0 - Unchanged / Grade 1 - Very little change / Grade 2 - Little change / Grade 3 - Change / Grade 4 - Strong Change

<sup>\*</sup>Except lodine - Grade 2 - Little change

Amorim Cork Flooring, S.A. Rua do Ribeirinho 202 - P.O. Box 13 4536-907 S. Paio de Oleiros - Portugal **T.** +351 22 747 56 00 **E.** info.acf@amorim.com



#### www.wicanders.com

| DE        | Amorim Deutschland GmbH (+49) 4221 5 93-01        | info.acf.de@amorim.com        |
|-----------|---|-------------------------------|
| BE NE LUX | Amorim Benelux B.V. (+31) 166 604 111             | info.acf.bnl@amorim.com       |
| AT        | Amorim Deutschland GmbH (+43) 154 51 65 10        | info.acf.at@amorim.com        |
| CH        | Amorim Flooring Switzerland AG (+41) 41 726 20 20 | info.acf.ch@amorim.com        |
| PT        | Amorim Revestimentos, S.A. (+351) 227 475 600     | info.acf@amorim.com           |
| ES        | Amorim Revestimentos, S.A. (+351) 227 475 600     | info.acf.es@amorim.com        |
| FR        | Amorim Revestimentos, S.A. (+33) 800 914 848      | info.acf.fr@amorim.com        |
| DK        | Timberman Denmark A/S (+45) 995 252 52            | timberman@timberman.dk        |
| PL        | Dom Korkowy, Sp. z o.o. (+48) 126 379 639         | krakow@domkorkowy.pl          |
| US        | Amorim Flooring North America (+1) 410 553 60 62  | info.acf.us@amorim.com        |
| RU        | Amorim Flooring Rus, OOO (+7) 495 280 7860        | info.acf.ru@amorim.com        |
| IT        | Amorim Revestimentos, S.A (+39) 800 790 805       | info.acf.it@amorim.com        |
| FI        | Korkkitrio Oy (+358) 50 554 2616                  | wicandersmyynti@korkkitrio.fi |
| SW        | Amorim Flooring Sweden (+46) 311 077 40           | info.acf.se@amorim.com        |
|           |   |                               |